

VIGON® EFM

Cleaning medium for manual flux removal



VIGON® EFM is a precision cleaning agent designed to remove flux residues from electronic assemblies in manual applications. This product can also be used in explosion -proof spray -in-air equipment. VIGON® EFM is a mixture of halogen -free organic solvents. It dries fast and residue -free. VIGON® EFM is non-corrosive and compatible with most polymers.

Areas of application: PCB's		Additional product information :
Resin-based flux residues*	++	Technical Information sheet 3 : Overview regarding material compatibility
Low solid flux residues*	0	
Water soluble flux residues*	-	

++ highly recommended, best results

+ recommended

0 possible

- not recommended

* Valid for all standard, lead-free and eutectic solder pastes

Technical Centers - ☒ America, ☒ Europe, ☒ Malaysia, ☒ North -China, ☒ South -China
Cleaning Process Solutions under Production Floor Conditions



Contact ZESTRON's Process Engineering Team for free-of-charge cleaning trials :

Phone: +49 -841 -635 -26; Email: techsupport@zestron.com

Advantages compared to other cleaners:

- ☒ VIGON® EFM is especially suitable for the removal of resin -based flux residues.
- ☒ This product dries very fast and residue -free.
- ☒ VIGON® EFM is easy -to-use.
- ☒ It can be used for both manual and automatic cleaning in explosion -proof equipment.
- ☒ Very suitable as a cleaning and rinsing agent.

Please refer to the material compatibility list (Technical Information 3) before cleaning plastics.



Process Steps	1. Cleaning	2. Rinsing	3. Drying
Spray-in-air	VIGON [®] EFM	VIGON [®] EFM	Compressed air or open air evaporation
Manual cleaning	VIGON [®] EFM	VIGON [®] EFM	Compressed air or open air evaporation

Technical Data		
Density	(g/ccm) at 20°C/68°C	0.72
Surface tension	(mN/m) at 25°C/77°F	18.6
Boiling range	°C/°F	78 - 120 / 172 - 248
Flash point	°C/°F	-12 / 10
pH-value	10g/l H ₂ O	Neutral
Vapor pressure	(mbar) at 20°C/68°F	Approx. 77
Solubility in water		Not Soluble
Cleaning temperature		Ambient Temperature
Application concentration	Ready-to-use	Readymix
HMIS Rating	Health -Flammability -Reactivity	1 - 4 - 0

PRODUCT FEATURES



Extensively tested and suitable for cleaning of lead-free solder pastes



Product is free of any critical substances according to SIN & SVHC lists



100% compliance with EU guidelines (RoHS 1 & 2, WEEE)

Environmental, health and safety regulations:

VIGON[®] EFM is biodegradable.

It is a highly flammable cleaning medium.

Refer to the MSDS for specific handling precautions and instructions.

Availability/Storage:

VIGON[®] EFM is available as an easy-to-use aerosol can with detachable brush for the manual removal of flux residues.

It is also available in 1l bottles, 25l or 55l containers and 200l drums.

Store VIGON[®] EFM in the original container at a temperature between

5°C - 30°C / 41 - 86°F.

The product has a minimum shelf life of 5 years in factory sealed containers.

Alternative product recommendation:



For the manual removal of SMT adhesive we recommend ZESTRON[®] HC.