

BL-5000



Suction (Vacuum) Attachment
BL-5000



Suction + Anti-electrostatic
BL-5000Q-ESD



Anti-electrostatic
BL-5000ESD



Clean Room
BLQ-5000CR



Clean

About variation

Feature

Thanks to ultra-powerful brushless motor, durability and stability have improved.

There is no carbon powder emission and maintains a clean environment.

Significant durability improvement considerably reduces maintenance cost.

Reduces the temperature rise of the motor by about 30% and mitigates problems related to heating.

Two types of start systems (push and lever) are available with one screwdriver (not applicable to BL-2000).

High-speed rotation shortens the tightening time and improves work efficiency.

BL-5000

Specification

Download

[Operation Manual \(pdf\)](#)

[DXF \(dxf\)](#)

Start

Output Torque Range

N · m

lbf · in

kgf · cm

Torque Switching

Unloaded Rotation Speed(r.p.m)

Low

High

Screw Size(mm)

Screw size

Tapping

Bit [\(selectable\)※](#)

Hios shank

Hex shank

Power Supply

Model

External Dimensions(mm)

Grip

Min

Max

Length(mm)

Weight(g)

Accessories

Bit

H4

H5

1/4HEX

Cord length(m)

Lshaped hexwrench

Torpue Range Table

Two-way(Push/Lever)Start Type
0.2-1.2
1.7-10
2-12
Stepless Adjustment
590
900
2-3
2-3
H4
H5 and 5HEX(both can be used)or1/4HEX
T-45BL T-70BL
32
38
207
360
+ #1 (∅ 4.0×40mm) + #2 (∅ 4.0×40mm)
+ #1 (∅ 5.0×60mm) + #2 (∅ 5.0×60mm)


+ #1 (5.0×50mm)

+ #2 (5.0×50mm)

- (5.0×50mm)

1.5m(5p)

Width cross flats:5mm,1pc



Series Comparison


Model

Start	
Output Torque Range	N · m lbf · in kgf · cm
Unloaded Rotation Speed(r.p.m)	Low High
Screw Size(mm)	Screw size Tapping
Bit Drive	Hios shank Hex shank

BL-2000




Lever Start Type
0.02-0.2
0.17-1.7
0.2-2
650
990
1-2.3
1-2
H4
-



BL-2000SS




Lever Start Type
0.02-0.2
0.17-1.7
0.2-2
650
990
1-2.3
1-2
H4
-



BL-3000



Two-way(Push/Lever)Start Type
0.2-0.55
1.7-4.8
2-5.5
680
980
1.7-2.3
2-2.3
H4
1/4HEX



Power Supply

T-45BL

DC Type

For DC screwdrivers Power Supply

T-70BL

DC Type

For DC screwdrivers Power Supply



Recommended Screw

HIOS PAT. Screw recess

HIOS own high-performance screws to improve the conventional problems.

Related Accessories

Vertical Screwdriver Operating Stand VMS-40

for BLG / BL / CL / SS / α / VZ (VZ-1510) Series

Vertical Screwdriver Operating Stand VMS-50

for PG / BLG / BL / CL / SS / α / VZ series



ScrewDriver
Torque Meter
Screw

Company
Outline
Message from the President
History
Awards
Branches
Employee's dog
ISO
Environment

Support
Contact
Distributor
FAQ
Download
Discontinued Products

About this website
News
Electric Screwdriver
General Catalog

株式会社 **ハイオス**

© 2021 HIOS Inc. ALL RIGHT RESERVED.