



innovative technology
for Turning The World

BLG-5000BC1-18



Suction(vacuum)Attachments BLG-5000BC1-18



About variation

Feature

No more overlooked tightening errors!

It prevents human errors in operations! It supports accurate screw tightening and reduces the operator's fatigue. A conventional external screw counter is not required. This realizes low-cost introduction of new screwdrivers. The integration of the screwdriver and the counter is optimal for space-saving operations.

Movie

No more overlooked tightening

errors!

(6:18)



BLG-5000BC1-18

Specification

Download

[Catalog \(digital catalog\)](#)

[Operation Manual \(pdf\)](#)

[Instruction Manual \(pdf\)](#)

[DXF \(dxf\)](#)

Start

Output Torque Range	N · m
	lbf · in
	kgf · cm

Torque Switching

Unloaded Rotation Speed(r.p.m)	Low
	High

Screw Size(mm)	Screw size
	Tapping

Bit <u>(selectable)※</u>	Hios shank
	Hex shank

Power Supply	Model
--------------	-------

External Dimensions(mm)	Grip
	Length(mm)

Weight(g)

Accessories	Bit	H5
		1/4HEX
		Cord length(m)
		Lshaped hexwrench

Torpue Range Table

Two-way(Push/Lever)Start Type

0.5-1.5

4.3-13

5-15

Stepless Adjustment

1200

1800

2.3-3

2-2.6

H5 and 5HEX(both can be used)

1/4HEX

T-70BL

38

235

425

+ #1 (\varnothing 5.0×60mm)

+ #2 (\varnothing 5.0×60mm)

+ #1 (5.0×50mm)

+ #2 (5.0×50mm)

- (5.0×50mm)

2m(6p)


L-shaped HEX wrench: WAF 5mm

N · m

1.4

1.2





Series Comparison

Model

Start	
Output Torque Range	N · m
	lbf · in
	kgf · cm
Unloaded Rotation Speed(r.p.m)	Low
	High
Screw Size(mm)	Screw size
	Tapping
Bit Drive	Hios shank
	Hex shank
Output Torque Range	kgf·cm
	0
	1
	5
	10
	20
	50
	100

BLG-4000BC1



Lever Start Type

0.1-0.55

0.9-4.8

1-5.5

690

1000

1.4-2.6

1.4-2.3

H4

1/4HEX

BLG-5000BC1



Two-way(Push/Lever)Start Type

0.2-1.2

1.7-10

2-12

690

1000

2.3-3

2-3

H4

H5 and 5HEX(both can be used)or1/4HEX

BLG-5000BC1-15



Two-way(Push/Lever)Start Type

0.3-1

2.6-10

3-10

1000

1500

2.3-3

2-2.6

H4

H5 and 5HEX(both can be used)or1/4HEX

● 1 (kgf·cm)
● 5.5 (kgf·cm)

● 2 (kgf·cm)
● 12 (kgf·cm)

● 3 (kgf·cm)
● 10 (kgf·cm)

Power Supply

T-70BL

DC Type

For DC screwdrivers Power Supply

Recommended Screw

HIOS PAT. Screw recess

HIOS own high-performance screws to improve the conventional problems.



Related Accessories

Vertical Screwdriver Operating Stand VMS-40

for BLG /BL/CL/SS/α /VZ(VZ-
1510)Series



Vertical Screwdriver Operating Stand VMS-50

for PG / BLG / BL / CL / SS / α /
VZseries



Related Items

BLOP-AF

DC Type

Relay box of complete signal



ScrewDriver
Torque Meter
Screw

Company
Outline
Message from the President
History
Awards
Branches
Employee's dog
ISO
Environment

Support
Contact
Distributor
FAQ
Download
Discontinued Products

About this website
News
Electric Screwdriver
General Catalog

株式会社 **ハイオス**

© 2021 HIOS Inc. ALL RIGHT RESERVED.