

JBC CDB

Soldering Station

JBC



Newly Upgraded!

More intuitive and well-connected

This station is **suitable for both SMD or THT components**.

It uses T245 General Purpose Handle the perfect tool for **general electronic applications with high power requirements**.

This station includes:

- Fast and easy configuration of the station thanks to the **7-key keypad**.
- **Cartridge Holder** to store up to four cartridges, as well as **Cartridge Extractor** and **Cable Collector**.
- Connectivity to JBC Fume Extractor (connector RJ12).

It provides the best soldering quality thanks to JBC Most Efficient Soldering System and, additionally, the Sleep & Hibernation Modes help to extend the life of tips.

**Don't believe us...
TRY IT!**



REFERENCES

CD-1BQF 120 V
CD-2BQF 230 V
CD-9BQF 100 V

PRODUCT COMPOSITION

- 1 CD Soldering Station
- 1 T245 General Purpose Handle (cartridge not included)

SPECIFICATIONS

Selectable Temperature	90 to 450 °C / 190 to 840 °F
CONNECTIVITY	
USB-B	Software PC / Firmware update
Equipotential bonding	Optional connection to EPA
RJ12 Connector	
Earthing Fuse	F 1.25A
ESD/EOS	
ESD safe	
Tip to ground vol./ resist.	Meets and exceed ANSI/ESD S20.20-2014 IPC J-STD-001F

POWER SUPPLY

Peak power	130 W - 23.5 V
Ambient operating temp.	10 to 50 °C / 50 to 120 °F

DIMENSIONS AND WEIGHT

Compact Stations	170 x 176 x 145 mm / 2.74 kg. 6.69 x 6.93 x 5.71 in / 6.04 lb.
Package	234 x 234 x 258 mm / 3.34 kg. 9.21 x 9.21 x 10.16 in / 7.36 lb.