

Stereo zoom microscope KERN OZP-5



LAB LINE

Professional and powerful – thanks to its extremely large magnification range, strong illumination and first-class optics

Features

- The KERN OZP stereo zoom microscope stands out through its above-average magnification range and its robust shape which is also ergonomic, it enables effortless, simple working over a period of several hours
- The KERN OZP series is available as a strong, continuously adjustable 3 W LED reflected and transmitted light variant for the very best illumination of your sample or as a variant without illumination
- With its large working distance, an extra large field of view and brilliant resolution, the KERN OZP provides sharp, high-contrast and colour-true images
- The extremely large, continuously adjustable magnification range from 6 to 55 times magnification means that you can work quickly and effectively
- There is a choice of a binocular model as well as a trinocular model for connecting a camera for documentation purposes and for quality reports
- The pillar stand is particularly flexible due to its variable and sturdy adjustment mechanism and therefore enables ergonomic working procedures
- A large selection of eyepieces, (universal) stands, a darkfield kit, external illumination units as well as auxiliary objectives and more are available as accessories
- A protective dust cover, eye cups, as well as multi-lingual user instructions are included in the scope of delivery
- A C-mount adapter is required to connect a camera to the trinocular version. You can select this adapter from the following model outfit list
- Please find detailed information in the following model outfit list

Scope of application

- Zoology and botany, quality control, electronics and semiconductor industry, assembly and repair

Applications/Samples

- Samples with focus on three-dimensional impression, zoom with variable magnification (depth, thickness), e.g. insects, seeds, circuit boards, components

Technical data

- Optical system: Greenough optics
- Brightness adjustable (separate)
- Tube: 35° inclined
- Magnification ratio: 9,2:1
- Light distribution OZP 557/558: 50:50
- Interpupillary distance 52 – 76 mm
- Diopter adjustment: Both-sided
- Overall dimensions W×D×H
330×285×470 mm
- Net weight approx. 4,5 kg

STANDARD



OPTION



Model	Standard configuration						
	Tube	Eyepiece	Field of view mm	Objective Zoom	Stand	Illumination	
KERN							
OZP 556	Binocular	HSWF 10×/ø 23 mm	ø 38,3 – 4,2	0,6× – 5,5×	Pillar style	3 W LED (incident); 3 W LED (transmitted)	
OZP 558	Trinocular	HSWF 10×/ø 23 mm	ø 38,3 – 4,2	0,6× – 5,5×	Pillar style	3 W LED (incident); 3 W LED (transmitted)	

Stereo zoom microscope KERN OZP-5

































Eyepiece	Specifications – Objectives					
	Magnification	Standard 1,0×	Auxiliary objectives			
			0,5×	0,7×	1,5×	2×
HSWF 10×	Total magnification	6× – 55×	3× – 27,5×	4,2× – 38,5×	9× – 82,5×	12× – 110×
	Field of view mm	∅ 38,3 – 4,2	∅ 76,7 – 8,4	∅ 54,8 – 6	∅ 25,6 – 2,8	∅ 19,2 – 2,1
SWF 15×	Total magnification	9× – 82,5×	4,5× – 41,25×	6,3× – 57,75×	13,5× – 123,75×	18× – 165×
	Field of view mm	∅ 28,3 – 3,1	∅ 56,7 – 6,2	∅ 40,5 – 4,4	∅ 18,9 – 2,1	∅ 14,2 – 1,5
SWF 20×	Total magnification	12× – 110×	6× – 55×	8,4× – 77×	18× – 165×	24× – 220×
	Field of view mm	∅ 23,3 – 2,5	∅ 46,7 – 5,1	∅ 33,3 – 3,6	∅ 15,6 – 1,7	∅ 11,7 – 1,3
SWF 30×	Total magnification	18× – 165×	9× – 82,5×	12,6× – 115,5×	27× – 247,5×	36× – 330×
	Field of view mm	∅ 15 – 1,6	∅ 30 – 3,3	∅ 21,4 – 2,3	∅ 10 – 1,1	∅ 7,5 – 0,8
Working distance		108 mm	195 mm	145 mm	50 mm	35 mm
Maximum sample height		110 mm	10 mm	45 mm	140 mm	150 mm

Model outfit		Model KERN		Order number	
		OZP 556	OZP 558		
Eyepieces (30,0 mm)	HSWF 10×/∅ 23 mm	✓✓	✓✓	OZB-A5503	
	SWF 15×/∅ 17 mm	○ ○	○ ○	OZB-A5504	
	SWF 20×/∅ 14 mm	○ ○	○ ○	OZB-A5505	
	SWF 30×/∅ 9 mm	○ ○	○ ○	OZB-A5506	
	HSWF 10×/∅ 23 mm (reticule 0,1 mm)	○	○	OZB-A5512	
	SWF 15×/∅ 17 mm (reticule 0,05 mm)	○	○	OZB-A5513	
	SWF 20×/∅ 14 mm (reticule 0,05 mm)	○	○	OZB-A5514	
Achromatic auxiliary objectives	0,5×	○	○	OZB-A5612	
	0,7×	○	○	OZB-A5613	
	1,5×	○	○	OZB-A5615	
	2,0×	○	○	OZB-A5616	
	Soldering protection lens	○	○	OZB-A5614	
C-Mount	0,3× (focus adjustable)		○	OZB-A5701	
	0,5× (focus adjustable)		○	OZB-A5702	
	1,0× (focus adjustable)		○	OZB-A5703	
	1,0× (with micrometer) only in combination with OZB-A5703		○	OZB-A5704	
	for SLR cameras (Nikon)		○	OZB-A5706	
	for SLR cameras (Olympus)		○	OZB-A5707	
	for SLR cameras (Canon)		○	OZB-A5708	
Darkfield unit	Darkfield unit	○	○	OZB-A4601	
Object clamp	Object clamp	○	○	OB-B-A6205	
Stand	Pillar style, without illumination				
	Pillar style, with 3 W LED illumination (transmitted + incident)	✓	✓		
	Please find more stands in the catalogue on page 84 and on the internet				
Stage plate	Frosted glass/∅ 94,5 mm		✓	OZB-A5192	
	Black-white/∅ 94,5 mm	✓	✓	OZB-A5191	
	Clear glass/∅ 94,5 mm		○	OZB-A5190	
Mechanical stage (Pre-assembling on request)	Stage size W×D 188×160 mm, Travel 76×65 mm, for incident and transmitted illumination	○	○	OZB-A5781	
	Stage size W×D 180×175 mm, Travel 100×86 mm, for incident illumination only	○	○	OZB-A5782	
External illumination	Please find the information about external illumination units in the catalogue on page 88 and on the internet				

✓ = Included with delivery

○ = Option

Pictograms

 360° rotatable microscope head	 Fluorescence illumination for compound microscopes With 3 W LED illumination and filter	 WLAN data interface For transmitting of the picture to a mobile display device
 Monocular Microscope For the inspection with one eye	 Phase contrast unit For a higher contrast	 HDMI digital camera For direct transmitting of the picture to a display device
 Binocular Microscope For the inspection with both eyes	 Darkfield condenser/unit For a higher contrast due to indirect illumination	 PC software To transfer the measurements from the device to a PC
 Trinocular Microscope For the inspection with both eyes and the additional option for the connection of a camera	 Polarising unit To polarise the light	 Automatic temperature compensation For measurements between 10 °C and 30 °C
 Abbe Condenser With high numerical aperture for the concentration and the focusing of light	 Infinity system Infinity corrected optical system	 Protection against dust and water splashes IPxx The type of protection is shown by the pictogram
 Halogen illumination For pictures bright and rich in contrast	 Zoom magnification For stereomicroscopes	 Battery operation Ready for battery operation. The battery type is specified for each device
 LED illumination Cold, energy-saving and especially long-life illumination	 Parallel optical system For stereomicroscopes, enables fatigue-proof working	 Battery operation rechargeable Prepared for a rechargeable battery operation
 Incident illumination For non-transparent objects	 Integrated scale In the eyepiece	 Mains adapter 230V/50Hz in standard version for EU. On request GB, AUS or USA version
 Transmitting illumination For transparent objects	 SD card For data storage	 Power supply Integrated in microscope. 230V/50Hz standard EU. More standards e.g. GB, AUS or USA on request
 Fluorescence illumination for stereomicroscopes	 USB 2.0 digital camera For direct transmitting of the picture to a PC	 Package shipment The time required to manufacture the product internally is shown in days in the pictogram
 Fluorescence illumination for compound microscopes With 100 W mercury lamp and filter	 USB 3.0 digital camera For direct transmitting of the picture to a PC	

Abbreviations

C-Mount	Adapter for the connection of a camera to a trinocular microscope	LWD	Long Working Distance	SWF	Super Wide Field (Field number at least Ø 23 mm for 10× eyepiece)
FPS	Frames per second	N.A.	Numerical Aperture	W.D.	Working Distance
H(S)WF	High (Super) Wide Field (Eyepiece with high eye point for wearers of glasses)	SLR camera	Single-Lens Reflex camera	WF	Wide Field (Field number up to Ø 22 mm for 10× eyepiece)

Your KERN specialist dealer: