

Video microscope KERN OIV-2



NEW



OIV 254 Snapshot button

The comprehensive digital solution for increased working comfort when carrying out continuous monitoring work in industry.

Features

- The Kern OIV is a video microscope which has been constructed to optimise digital stereo microscopy. Our well-conceived, comprehensive solution with axial optical unit enables immediate, simple display of your samples on the screen.
- The LED incident illumination unit (ring) included as standard guarantees the very best illumination of your sample.
- Combined with the large working surface, recording objects on the screen is ideally suited for monitoring, analysis and documentation in industrial environments.
- The excellent optical unit enables continuous sharp image tracking across the entire zoom range from 0.7×–5×.
- The powerful 2.0 megapixel camera of the microscope without eyepieces offers, thanks to the HDMI output, smooth live monitoring of your samples from the HD monitor. In addition, the software which is easy to use, the USB stick as well as the USB mouse which are integral components of the delivery, mean you can process and store your results digitally.
- With the OIV 254 model, there is the option of image documentation at the push of a button, without having to detour via the software. On the other hand, the OIV 255 guarantees software-controlled taking of images and videos with additional, extensive measuring functions.
- A protective dust cover, as well as multi-lingual user instructions are included in the scope of the delivery

Technical data

- Optical system: Axial
- Brightness adjustable
- Screen: 12", 1920×1080 HD, -5°–15° inclination
- Magnification ratio: 7,1:1
- Stand: arm curved
- Illumination: 2 W LED ring (incident)
- Data storage: External using USB (Max 128 GB)
- Overall dimensions W×D×H 320×260×483 mm
- Net weight approx. 10 kg

Accessories

- Auxiliary objective 0,5×, KERN OZB-A2101

STANDARD



Model	Standard configuration						
	Resolution camera	Interface	Sensor	Field of view mm	Objective Zoom	Software functions	
KERN							
OIV 254	2 MP	HDMI (60 FPS)	CMOS 1/2"	∅ 29,82–4,18	0,7×–5×	Image capture	
OIV 255	2 MP	HDMI (60 FPS)	CMOS 1/2"	∅ 29,82–4,18	0,7×–5×	Images and videos, measurements	

Pictograms

 360° rotatable microscope head	 Fluorescence illumination for compound microscopes With 3 W LED illumination and filter	 WLAN data interface For transmitting of the picture to a mobile display device
 Monocular Microscope For the inspection with one eye	 Phase contrast unit For a higher contrast	 HDMI digital camera For direct transmitting of the picture to a display device
 Binocular Microscope For the inspection with both eyes	 Darkfield condenser/unit For a higher contrast due to indirect illumination	 PC software To transfer the measurements from the device to a PC
 Trinocular Microscope For the inspection with both eyes and the additional option for the connection of a camera	 Polarising unit To polarise the light	 Automatic temperature compensation For measurements between 10 °C and 30 °C
 Abbe Condenser With high numerical aperture for the concentration and the focusing of light	 Infinity system Infinity corrected optical system	 Protection against dust and water splashes IPxx The type of protection is shown by the pictogram
 Halogen illumination For pictures bright and rich in contrast	 Zoom magnification For stereomicroscopes	 Battery operation Ready for battery operation. The battery type is specified for each device
 LED illumination Cold, energy-saving and especially long-life illumination	 Parallel optical system For stereomicroscopes, enables fatigue-proof working	 Battery operation rechargeable Prepared for a rechargeable battery operation
 Incident illumination For non-transparent objects	 Integrated scale In the eyepiece	 Mains adapter 230V/50Hz in standard version for EU. On request GB, AUS or USA version
 Transmitting illumination For transparent objects	 SD card For data storage	 Power supply Integrated in microscope. 230V/50Hz standard EU. More standards e.g. GB, AUS or USA on request
 Fluorescence illumination For stereomicroscopes	 USB 2.0 digital camera For direct transmitting of the picture to a PC	 Package shipment The time required to manufacture the product internally is shown in days in the pictogram
 Fluorescence illumination for compound microscopes With 100 W mercury lamp and filter	 USB 3.0 digital camera For direct transmitting of the picture to a PC	

Abbreviations

C-Mount	Adapter for the connection of a camera to a trinocular microscope	LWD	Long Working Distance	SWF	Super Wide Field (Field number at least Ø 23 mm for 10× eyepiece)
FPS	Frames per second	N.A.	Numerical Aperture	W.D.	Working Distance
H(S)WF	High (Super) Wide Field (Eyepiece with high eye point for wearers of glasses)	SLR camera	Single-Lens Reflex camera	WF	Wide Field (Field number up to Ø 22 mm for 10× eyepiece)

Your KERN specialist dealer: