


Tablet Camera KERN ODC-2



ODC 241



Integrated software with measuring function

Digital microscopy brought up to date – tablet with integrated camera for optimal observation and digital documentation of the sample

Features

- A 2-in-1 solution in digital microscopy as a universal system for trinocular microscopes with C-mount adapter. The ODC 241 microscope-tablet-camera consists of a large Android tablet in combination with a 5-MP camera
- The KERN ODC 241 tablet-camera has been specially developed for simple and direct observation of the sample on the screen. Ideally suited for school pupils and students in education or for demonstration purposes in the laboratory
- As well a live transfer of the image to the Android table, the integrated 5-MP camera also means that images and videos can be created for the documentation.
- Simple measuring functions such as, for example, functions for measuring distance, surfaces and angles as well as a manual counting function are also available
- Automatic white balance and automatic contrast adjustment can be performed quickly and easily, which enables efficient working procedures
- A range of additional functions are provided through the integrated interfaces, such as, for example
 - Data storage on a USB stick or SD card
 - Connection to a USB mouse
 - Transfer of the live image to an external screen using HDMI
 - Transfer of stored data to external receivers using WLAN
- The delivery includes the tablet camera with pre-installed software as well as the mains adapter

Technical data

- 9.7" LCD-Touchscreen
- Screen resolution: 2048×1536 pixels
- CPU: Quad Core Cortex-A17; 1,8 GHz
- Overall dimensions W×D×H 238×51×206 mm
- Net weight approx. 0,65 kg

STANDARD



Model	Resolution Camera	Interface	FPS	Sensor	Sensor size	Supported operating system	
KERN							
ODC 241	5 MP	WLAN, USB 2.0, HDMI, SD	15 – 30	CMOS	1/2,5"	Android 5.1	

Pictograms

 360° rotatable microscope head	 Fluorescence illumination for compound microscopes With 3 W LED illumination and filter	 WLAN data interface For transmitting of the picture to a mobile display device
 Monocular Microscope For the inspection with one eye	 Phase contrast unit For a higher contrast	 HDMI digital camera For direct transmitting of the picture to a display device
 Binocular Microscope For the inspection with both eyes	 Darkfield condenser/unit For a higher contrast due to indirect illumination	 PC software To transfer the measurements from the device to a PC
 Trinocular Microscope For the inspection with both eyes and the additional option for the connection of a camera	 Polarising unit To polarise the light	 Automatic temperature compensation For measurements between 10 °C and 30 °C
 Abbe Condenser With high numerical aperture for the concentration and the focusing of light	 Infinity system Infinity corrected optical system	 Protection against dust and water splashes IPxx The type of protection is shown by the pictogram
 Halogen illumination For pictures bright and rich in contrast	 Zoom magnification For stereomicroscopes	 Battery operation Ready for battery operation. The battery type is specified for each device
 LED illumination Cold, energy-saving and especially long-life illumination	 Parallel optical system For stereomicroscopes, enables fatigue-proof working	 Battery operation rechargeable Prepared for a rechargeable battery operation
 Incident illumination For non-transparent objects	 Integrated scale In the eyepiece	 Mains adapter 230V/50Hz in standard version for EU. On request GB, AUS or USA version
 Transmitting illumination For transparent objects	 SD card For data storage	 Power supply Integrated in microscope. 230V/50Hz standard EU. More standards e.g. GB, AUS or USA on request
 Fluorescence illumination For stereomicroscopes	 USB 2.0 digital camera For direct transmitting of the picture to a PC	 Package shipment The time required to manufacture the product internally is shown in days in the pictogram
 Fluorescence illumination for compound microscopes With 100 W mercury lamp and filter	 USB 3.0 digital camera For direct transmitting of the picture to a PC	

Abbreviations

C-Mount	Adapter for the connection of a camera to a trinocular microscope	LWD	Long Working Distance	SWF	Super Wide Field (Field number at least Ø 23 mm for 10× eyepiece)
FPS	Frames per second	N.A.	Numerical Aperture	W.D.	Working Distance
H(S)WF	High (Super) Wide Field (Eyepiece with high eye point for wearers of glasses)	SLR camera	Single-Lens Reflex camera	WF	Wide Field (Field number up to Ø 22 mm for 10× eyepiece)

Your KERN specialist dealer: