



3H OIL FG

NSF 3H AND H1 MULTI-PURPOSE OIL

3H Oil FG is a lubricating and release oil that can be used in applications where direct food contact is likely. The light oil film can also be used as an anticorrosion treatment on metal surfaces such as meat hooks and tables.

3H Oil FG is non-tainting and clear. Ideal for use on mixing and processing equipment to prevent food adhering. Light oil seals out moisture and helps prevent corrosion.



Lubricants



NSF Registered:
category 3H & H1
no. 148343



Halal Certified Product:
AN001183

PRODUCT CODES / FILL SIZES



32326 / 5Ltr

APPLICATIONS

- Bakery equipment
- Meat/poultry processing + packing equipment
- Bottle filling machinery
- Stainless steel pumps
- Rollers
- General lubrication during equipment installation

DIRECTIONS

- Do not use on energised (live) equipment.
- Apply a light, even film.
- Allow a short time for penetration before use.
- Wipe off excess with cloth.
- Repeat application when necessary.

TECHNICAL DATA (WITHOUT PROPELLANT)

Appearance	Clear, colourless liquid
Specific Gravity (@ 20°C)	0.850
Colour, Saybolt (Min)	+30
Kinematic Viscosity (@ 40°C)	17 mm ² /s
Flash Point (open cup)	180°C
Pour Point	-6°C
Temperature Range	-5°C to +120°C
Based upon the present state of our knowledge and information received from our suppliers, evaluation of this product indicates that it is free from nut oils and their derivatives.	

MATERIALS COMPATIBILITY

OK	-
CAUTION	-
NOT OK	-

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via info.uk@crcind.com

MISREPRESENTATION ACT 1967

TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 4.0
Created: July 2019
Updated: June 2021

CRC Industries UK Ltd.
Wylds Road, Bridgwater
Somerset, TA6 4DD
United Kingdom

Company Registered No. 04910479

t +44 (0)1278 727200
f +44 (0)1278 425644
e sales.uk@crcind.com
w www.ambersil.com

VAT No. GB 821 5195 42

