



Polymer Processing



High Temperature Resistant

GRAPHITE RELEASE SPRAY

DRY GRAPHITE LUBRICANT & RELEASE AGENT

Graphite Release Spray is a high purity, dry, concentrated graphite lubricant and release agent containing fine graphite particles in a thermoplastic binder. It adheres strongly to metal, plastics, glass, and many other surfaces which require a highly effective anti-friction coating.

Graphite Release Spray has been primarily formulated for use in the glass blowing and forming industry where it is used as a mould pre-treatment, as a molten glass flow improver and as a release agent.

PRODUCT CODES / FILL SIZES



32499 / 400ml

APPLICATIONS

- Glass moulding – mould pre-treatment and release agent
- Glass moulding (gob) flow improver
- Glass industry general and guide lubricant
- Dry film industrial lubricant
- Static discharge coating
- Electrically conductive contact lubricant

DIRECTIONS

- Shake can thoroughly before use.
- Ensure that surfaces are dry and free from oil and grease (degrease with an Ambersil solvent cleaner if necessary).
- Apply a light, even coating from a distance of 15-25 cm.
- Once cured the film can be lightly burnished in order to provide a high quality finish to glassware.
- After use, always clean the actuator orifice by spraying upside-down until only gas escapes.
- At temperatures above 100°C the binding agent will decompose, leaving a graphite film that can be used as a release coating.

TECHNICAL DATA (WITHOUT PROPELLANT)

Appearance	Black
Flashpoint	11°C
Coverage – calculated (20µm thickness)	0.6m ² /400ml aerosol
Drying time at room temperature	Touch dry in approx. 20 min. Fully cured in 4 hours
Temperature resistance of lacquer	90°C approx.
Temperature resistance of graphite film	250°C -300°C

MATERIALS COMPATIBILITY

OK	-
CAUTION	-
NOT OK	-

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 4 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via info.uk@crcind.com

MISREPRESENTATION ACT 1967

TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 3.1
Created: July 2019
Updated: October 2020

CRC Industries UK Ltd.
Wylds Road, Bridgwater
Somerset, TA6 4DD
United Kingdom

Company Registered No. 04910479

t +44 (0)1278 727200
f +44 (0)1278 425644
e sales.uk@crcind.com
w www.ambersil.com

VAT No. GB 821 5195 42

