

GX-H Series

40 Volts • Auto-shut off • CE • XS-40D Controller 

0,3 to 4,4 NM



- Higher productivity : thanks to high Brushless motor efficiency !
- Higher comfort : thanks to improved ergonomoy and reduced sound level and heat !
- Increased economy : thanks to brushless motor (triple the life time of the motor).
- Reduced maintenance : the best Mean Time Between Failure (MTBF) ever reached until now (no carbon brush, trigger and reverse contactless switches, over-heat and over-current built in alarms protecting the screwdrivers).
- Increased production quality : thanks to ESD protection, accurate clutch and Softstop clutch Mechanism.
- Noise level : <70 dBA, vibration level : <2,5 m/s²

STANDARD Series : GX with digital speed setting and soft start

Model	Torque Range (Nm)	Speed rotation (rpm)	Starting system	Drive	Weight (Kg)	Code
GX 150 ESD-H	0,3 - 1,47	800 to 1700	Lever	Hex 1/4"	0,60	4-1027477
GX 220 ESD-H	0,6 - 2,15	600 to 1200	Lever	Hex 1/4"	0,60	4-1027478
GX 450 ESD-H	1 - 4,41	300 to 600	Lever	Hex 1/4"	0,62	4-1027479
GX 150 P ESD-H	0,3 - 1,47	800 to 1700	Push to Start	Hex 1/4"	0,60	4-1027480
GX 220 P ESD-H	0,6 - 2,15	600 to 1200	Push to Start	Hex 1/4"	0,60	4-1027481
GX 450 P ESD-H	1 - 4,41	300 to 600	Push to Start	Hex 1/4"	0,62	4-1027482

Suitable controller : XS-40D - To be ordered separatly - See page 17

SOFT STOP Series : GXS (built-in special clutch mechanism providing soft shut-off to protect fragile parts)

Model	Torque Range (Nm)	Speed rotation (rpm)	Starting system	Drive	Weight (Kg)	Code
GXS 150 ESD-H	0,3 - 1,47	800 to 1700	Lever	Hex 1/4"	0,60	4-1027486
GXS 220 ESD-H	0,6 - 2,15	600 to 1200	Lever	Hex 1/4"	0,60	4-1027487

Suitable controller : XS-40D - To be ordered separatly - See page 17

TIMER & AUTOREVERSE Series : GXT (fasten at preset angle/time, Automatic Reverse/forward stop sequence - ideal for tapping operation, helicoil fastening, pre-assembly...)

Model	Torque Range (Nm)	Speed rotation (rpm)	Starting system	Drive	Weight (Kg)	Code
GXT 150 ESD-H	0,3 - 1,47	800 to 1700	Lever	Hex 1/4"	0,60	4-1027489
GXT 220 ESD-H	0,6 - 2,15	600 to 1200	Lever	Hex 1/4"	0,60	4-1027490
GXT 450 ESD-H	1 - 4,41	300 to 600	Lever	Hex 1/4"	0,62	4-1027491

Suitable controller : XS-40D - To be ordered separatly - See page 17

FIXTURED SPINDLE FOR AUTOMATION (for automation choose XS-40D FA controller - Code 4-1040080)

Model	Torque Range (Nm)	Speed rotation (rpm)	Starting system	Drive	Weight (Kg)	Code
GXA 150-H	0,3 - 1,47	800 to 1700	Remote	Hex 1/4"	0,72	4-1027483
GXA 220-H	0,6 - 2,15	600 to 1200	Remote	Hex 1/4"	0,72	4-1027484
GXA 450-H	1 - 4,41	300 to 600	Remote	Hex 1/4"	0,74	4-1027485
GXA 150P-H	0,3 - 1,47	800 to 1700	Push to start	Hex 1/4"	0,79	4-1027492
GXA 220P-H	0,6 - 2,15	600 to 1200	Push to start	Hex 1/4"	0,79	4-1027493
GXA 450P-H	1 - 4,41	300 to 600	Push to start	Hex 1/4"	0,74	4-1027494

* The whole models of this series are delivered with one tool cable (3m) + sample powerbits.

Controllers

SMPS Technology Inside!



XS-40D

- High productivity : Thanks to the unique SMPS technology (switching modulation), the connected screwdriver always delivers constant rotation speed and fastening force even for demanding fastening process (self-tapping tightening, soft joint....).
- Comfort : Light and compact.
- Durability : Built-in Over heat and Over Current protection prevent the screwdriver from damage or bad use.
- Economy : Maintenance free.
- Quality : Easy monitoring of your fastenings thanks to torque reached signal output, start and stop signal outputs, selectable softstart, Screwdriver lock signal input for PLC (prevents screwdrivers activation until PLC input signal).

Model	Power (AC) (V)	Output voltage low (V)	Output voltage high (V)	Rated output (A)	Weight (Kg)	Size (mm)	For screwdrivers 30 and 40 Volts	Code
XS-40D	220	30	40	3	0,86	90x150x55	GX, GX-G, GX...FS/GX-H Series	4-1040065
XS-40D FA	220	30	40	3	0,86	90x150x55	GXA, GXA-G, GXA-H Series	4-1040080

SMPS Technology Inside!



XS-38D

XT-30D

- High productivity : Thanks to the unique **SMPS technology** (switching modulation), the connected screwdriver always delivers constant rotation speed and fastening force even for demanding fastening process (self-tapping tightening, soft joint....)
- Comfort : Light weight and compact
- Durability : Built-in Over heat and Over Current protection prevent the screwdriver from damage or bad use
- Economy : Maintenance free
- Quality : Easy monitoring of your fastenings thanks to torque reached signal output, start and stop signal outputs, selectable softstart, Double-hit mode for soft joint, Screwdriver lock signal input for PLC (prevents screwdrivers activation until PLC input signal).

Model	Power (AC) (V)	Output voltage low (V)	Output voltage high (V)	Rated output (A)	Max. output (A)	Weight (Kg)	Size (mm)	For screwdrivers	Code
XT-30D-V2	220	20	30	1,2	2	0,33	70x130x40	GA Series	4-1099550
XS-38D V4.3*	220	30 20	38 30	2,5	5	0,7	90x150x55	DO Series GA Series	4-1040063