



BASIC



03

Quick-display precision balance with user-friendly concept of operation mode – now with larger housing for more stability

Features

- Easy to use: All primary functions have their own key on the keypad
- Compact size, practical for small spaces
- Capacity display: A bargraph display lights up to show how much of the weighing range is still available
- Level indicator and levelling feet for precise levelling of the scale, fitted as standard, to give the most accurate weighing result
- Draught shield standard for models with weighing plate size **A** Ø 80 mm, **B** Ø 120 mm, Weighing space W×D×H 116×111×65 mm

Technical data

- Backlit LCD display, digit height 15 mm
- Dimensions weighing surface, stainless steel
 - A** Ø 80 mm
 - B** Ø 120 mm
 - C** W×D 190×180 mm, see larger picture
- Overall dimensions (without draught shield) W×D×H 210×315×90 mm
- Permissible ambient temperature 15 °C/30 °C

Accessories

- Protective working cover, scope of delivery 5 items, KERN PFB-A12S05, **€ 44,-**
- Bluetooth data interface for wireless data transfer to PC or tablets, must be ordered at purchase
 - Bluetooth 2.0: KERN PFB-A10, **€ 105,-**
 - Bluetooth 4.0: KERN PFB-A11, **€ 155,-**
- Further details, plenty of further accessories and suitable printers see *Accessories*


STANDARD



OPTION



FACTORY



Model	Weighing capacity	Readability	Reproducibility	Linearity	Weighing plate	Price excl. of VAT ex works €	Option DAkkS Calibr. Certificate DAkkS KERN	€
KERN	[Max] g	[d] g	g	g				
PFB 120-3	120	0,001	0,001	± 0,003	A	400,-	963-127	93,-
PFB 200-3	200	0,001	0,002	± 0,005	A	410,-	963-127	93,-
PFB 300-3	300	0,001	0,002	± 0,005	A	450,-	963-127	93,-
PFB 600-2	600	0,01	0,01	± 0,03	B	330,-	963-127	93,-
PFB 1200-2	1200	0,01	0,01	± 0,03	B	345,-	963-127	93,-
PFB 2000-2	2000	0,01	0,02	± 0,05	B	370,-	963-127	93,-
PFB 3000-2	3000	0,01	0,02	± 0,05	B	395,-	963-127	93,-
PFB 6000-2	6000	0,05	0,05	± 0,15	C	350,-	963-128	112,-
PFB 6000-1	6000	0,1	0,1	± 0,3	C	300,-	963-128	112,-