



Cleaners



360° Spray System for all angle use



MOD Approval

AMBERKLENE FE10

FAST DRYING SOLVENT

Amberklene FE10 is a fast evaporating solvent blend which contains no CFCs or other chlorinated solvents. It is an ideal alternative to 1,1,1 Trichloroethane.

A highly effective degreasing agent for all hydrocarbon soiling, including oil, grease, tar and bitumen, can be used for general degreasing of machinery including chains, gears, bearings, drives, motors, and more. For use in numerous industries including where a fast and effective cleaning solvent is required.

PRODUCT CODES / FILL SIZES



31553 / 400ml



31634 / 5Ltr



30308 / 25Ltr



31697 / 200Ltr

APPLICATIONS

- Degreasing Bearings
- Surface preparation prior to painting
- Spot removal for textiles
- Mould tool degreaser/ cleaner
- Precision engine component degreaser
- Offshore
- Printing
- Agriculture
- Aviation
- Marine
- Light and Heavy Engineering

DIRECTIONS

- Efficiently cleans ferrous and non-ferrous metals, evaporating quickly to leave a clean, dry surface.
- Also recommended for spot removal in the textiles and associated industries.
- May affect certain plastics. Always test a small, inconspicuous area before general use.
- Ensure electrical equipment is switched off before cleaning.

TECHNICAL DATA (WITHOUT PROPELLANT)

Appearance	Clear, colourless liquid
Odour	Mild and sweet
Specifications/Approvals	NATO Catalogue No. 6850-99-6636478
SG @ 25°C	0.770
Pressure @ 25°C	5 - 6 Bar
Discharge rate	2.5 g/sec
Kb value	75
Initial boiling point	64°C
Freezing point	Below -50°C
Evaporation rate	6.0 (with respect to Butyl Acetate)
Flammability	Classified as extremely flammable under Current EC Regulations
Flashpoint	-18°C (Bulk)

MATERIALS COMPATIBILITY

OK	Ferrous and non-ferrous metals
CAUTION	May affect certain plastics. Always test a small, inconspicuous area before general use
NOT OK	-

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via info.uk@crcind.com

MISREPRESENTATION ACT 1967

TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 3.1
Created: July 2019
Updated: October 2020

CRC Industries UK Ltd.
Wylds Road, Bridgwater
Somerset, TA6 4DD
United Kingdom

t +44 (0)1278 727200
f +44 (0)1278 425644
e sales.uk@crcind.com
w www.ambersil.com

Company Registered No. 04910479

VAT No. GB 821 5195 42

