



Polymer Processing

## GREEN MOULD PROTECTIVE

### HIGH VISIBILITY, ANTI-CORROSION PROTECTION

Green Mould Protective provides long term protection to mould tool surfaces after use. It removes any surface moisture and protects the mould tool against corrosion during storage. Green Mould Protective will not penetrate or creep into the mould tool. It has a highly visible film that offers easy identification, total coverage assured. It resists acid finger markings and it's easily moulded off, ensuring quick start up. The mould tool remains in top condition.

### PRODUCT CODES / FILL SIZES



31546 / 400ml

### APPLICATIONS

A coloured, non-silicone, protective coating for use on mould tools. It incorporates a highly visible green tracer dye for easy visual identification, ensuring complete coverage and, thus total protection. The viscous consistency prevents “run-off” and inhibits creeping into the mould tool.

The film resists the effects of high humidity. It will not harden or crack and is easily moulded off when recommencing production. Alternatively, it may be removed with Ambersil Mould Cleaner or any of the Amberklene Solvents.

- All injection mould tools, blow mould tools, extrusion dies and metal components requiring corrosion protection.

### DIRECTIONS

- Apply a light, even coating to all surfaces from 9” - 12” (25-30cm).
- Ensure that the surfaces have cooled to below 35°C to ensure optimum film formation.

## TECHNICAL DATA (WITHOUT PROPELLANT)

Appearance	Viscous, Green Film
Protection Against Corrosion	TBA
Water Displacing	TBA
Salt Spray Test	TBA
Film Forming Properties	A continuous, homogenous film remains after 10 minutes
Solubility	Soluble in solvents, insoluble in water
Flammability	Classified as extremely flammable under current EC Regulations
Flashpoint	Not applicable in sealed aerosol

## MATERIALS COMPATIBILITY

OK	-
CAUTION	-
NOT OK	-

## STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

## HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via [info.uk@crcind.com](mailto:info.uk@crcind.com)

## MISREPRESENTATION ACT 1967

## TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 3.1  
Created: July 2019  
Updated: October 2020

CRC Industries UK Ltd.  
Wylds Road, Bridgwater  
Somerset, TA6 4DD  
United Kingdom

Company Registered No. 04910479

t +44 (0)1278 727200  
f +44 (0)1278 425644  
e [sales.uk@crcind.com](mailto:sales.uk@crcind.com)  
w [www.ambersil.com](http://www.ambersil.com)

VAT No. GB 821 5195 42

