







## Orthomat® Standard

Quickly tackle standing fatigue in dry workplaces



- Versatile single layer foam anti-fatigue mat.
- Insulates standing workers against the effects of cold concrete floors.
- Lightweight, so easy to transport and reposition.
- Best suited to dry environments.
- High visibility version available with bright yellow borders.
- Ideal for lighter industrial use.
- Textured surface provides attractive appearance.
- Available in mats and rolls.
- Fire tested to BS EN 13501-1.



Styles Available

Black

Grey

Safety

## Parts

| Part Number | Size                     | Colour       | Weight (kg) |
|-------------|--------------------------|--------------|-------------|
| AF010001    | 0.6 m x 0.9 m            | Black        | 1.31        |
| AF010002    | 0.9 m x 1.5 m            | Black        | 3.27        |
| AF010003    | 0.9 m x 18.3 m           | Black        | 40          |
| AF010003C   | 0.9 m x per linear metre | Black        | 1.6         |
| AF010004    | 0.45 m x 0.9 m           | Black        |             |
| AF010005    | 1.2 m x 18.3 m           | Black        | 58.55       |
| AF010005C   | 1.2 m x per linear metre | Black        | 2.1         |
| AF010701    | 0.6 m x 0.9 m            | Black/Yellow | 1.31        |
| AF010702    | 0.9 m x 1.5 m            | Black/Yellow | 3.27        |
| AF010703    | 0.9 m x 18.3 m           | Black/Yellow | 40          |
| AF010703C   | 0.9 m x per linear metre | Black/Yellow | 3.01        |
| AF010706    | 1.2 m x 18.3 m           | Black/Yellow | 70          |
| AF010706C   | 1.2 m x per linear metre | Black/Yellow | 2.1         |
| AF060001    | 0.6 m x 0.9 m            | Grey         | 1.31        |
| AF060002    | 0.9 m x 1.5 m            | Grey         | 3.27        |
| AF060003    | 0.9 m x 18.3 m           | Grey         | 40          |
| AF060003C   | 0.9 m x per linear metre | Grey         | 2           |

## Technical Specifications

|                                                         |                                                                 |
|---------------------------------------------------------|-----------------------------------------------------------------|
| Material                                                | Open Cell PVC (Foam)                                            |
| Surface Finish                                          | Pebble                                                          |
| Product Height                                          | 9.5 mm                                                          |
| Roll Length                                             | 18.3 m                                                          |
| Size of Safety Border                                   | 100 mm                                                          |
| Min. Operating Temperature                              | 0°C                                                             |
| Max. Operating Temperature                              | +60°C                                                           |
| Environmental Resistance                                | Suitable for dry indoor environments                            |
| Typical Applications                                    | Production lines, Assembly areas, Packing stations, Workbenches |
| Installation Method                                     | Loose lay                                                       |
| Cleaning Method                                         | Brush/mop the top surface                                       |
| Fire Tested to                                          | BS EN 13501-1 Class Dfl - s1                                    |
| COO (Country of Origin)                                 | CN                                                              |
| Guarantee                                               | 1 year when used in a dry environment                           |
| Adhesive recommended by F.Ball for permanent bond       | F44                                                             |
| Tackifier recommended by F.Ball                         | F41                                                             |
| Adhesive recommended by F.Ball for heavy-duty/wet areas | F74, F81, F84                                                   |

## Additional Information



Orthomat Fire Test BS EN 13501



Orthomat Fire Test EN ISO 11925



Orthomat Fire Test EN ISO 9239

