



HS Series Screw Feeder have been remodeled as a high cost-performance model and will be launched on November 4th.




Nov 4th, 2025 on Sale

— Automatic Screw Feeder —



HSV/HSV-

| HS/HS-

HSV/HSV-RB




Specifications

Model	HSV	HSV-RB
Category	Manual	Automation
	Rotary Escaper	Rotary Escaper
Screws taken out by		
Screw Capacity	80cc	
O/L Protection Circuit	●	●
External Output Signal	●	●
Power	IN : AC100-240V 50/60Hz OUT : DC15V 2.4A	
Weight	3.0 kg	
Dimensions (mm)	123 × 181 × 146	


Range of Feedable Screws

Model	Order Code	Nominal Dia.	Shaft Dia.	Head Dia.	Head Thickness	Thread Length
HSV	JHSV-10	1.0	0.9-0.95	1.8-4.5	0.35-1.0	1.6-10
	JHSV-12	1.2	1.1-1.15	1.8-4.5	0.35-1.0	1.9-10
	JHSV-14	1.4	1.3-1.4	2.0-4.5	0.35-1.0	2.2-10
	JHSV-17	1.7	1.6-1.7	2.0-4.5	0.35-1.0	2.7-10
	JHSV-20	2.0	1.9-2.1	3.0-6.0	0.35-4.0	3.2-20
	JHSV-23	2.3	2.2-2.4	3.3-6.0	0.35-4.0	3.7-20
	JHSV-26	2.6	2.5-2.7	3.6-6.0	0.35-4.0	4.2-20
	JHSV-30	3.0	2.9-3.2	4.0-6.0	0.35-4.0	4.8-20
HSV-RB	JHSV-10RB	1.0	0.9-0.95	1.8-4.5	0.35-1.0	1.6-10
	JHSV-12RB	1.2	1.1-1.15	1.8-4.5	0.35-1.0	1.9-10
	JHSV-14RB	1.4	1.3-1.4	2.0-4.5	0.35-1.0	2.2-10
	JHSV-17RB	1.7	1.6-1.7	2.0-4.5	0.35-1.0	2.7-10
	JHSV-20RB	2.0	1.9-2.1	3.0-6.0	0.35-4.0	3.2-20
	JHSV-23RB	2.3	2.2-2.4	3.3-6.0	0.35-4.0	3.7-20
	JHSV-26RB	2.6	2.5-2.7	3.6-6.0	0.35-4.0	4.2-20
	JHSV-30RB	3.0	2.9-3.2	4.0-6.0	0.35-4.0	4.8-20

HS/HS-RB



Specifications

Model	HS	HS-RB
Category	Manual	Automation
	Linear Rail	Slide Escaper
Screws taken out by		
Screw Capacity	150cc	
O/L Protection Circuit	●	●
External Output Signal	●	●
Power	IN : AC100-240V 50/60Hz OUT : DC15V 2.4A	
Weight	3.7Kg	4.4Kg
Dimensions (mm)	130 × 215 × 139	134 × 274 × 139

Range of Feedable Screws

Model	Order Code	Nominal Dia.	Shaft Dia.	Head Dia.	Head Thickness	Thread Length
HS	JHS-35	3.5	3.3-3.7	4.8-8.0	0.5-8.0	5.6-18
	JHS-40	4.0	3.8-4.1	5.4-8.0	0.5-8.0	6.4-18
	JHS-50	5.0	4.8-5.1	6.2-10	0.5-8.0	8.0-18
HS-RB	JHS-35RB	3.5	3.3-3.7	4.8-8.0	0.5-8.0	5.6-18
	JHS-40RB	4.0	3.8-4.1	5.4-8.0	0.5-8.0	6.4-18
	JHS-50RB	5.0	4.8-5.1	6.2-10	0.5-8.0	8.0-18